

## **BAND-ADE®**

### **Semi-Synthetic Sawing Fluid**

General purpose flood coolant designed for light to moderate-duty machining applications involving both ferrous and non-ferrous metals

**EXTENDS BLADE LIFE**

Increased lubrication aids in chip formation and evacuation

**EXCEPTIONAL COOLING**

Water-soluble formulation helps to reduce frictional heat and improves cutting performance

**INCREASES PRODUCTIVITY**

Faster cutting and reduced machine wear increases efficiency

**ENVIRONMENTALLY FRIENDLY**

Products are biodegradable, safe for the operator to use, and do not contain harmful chemicals like chlorine and sulphur

**SURFACES CAN BE WELDED AND PAINTED OVER**



PROD NO	CONTAINER SIZE (LITER)	CONTAINERS PER CASE
1988851	5 liter	case of 2
1988852	25 liter	—
1988853	200 liter drum	—

*Not recommended for use as a spray lubricant. Mix this product with water as recommended*

RATIO	REFRACTOMETER
10:1 (10%)	3.5
15:1 (6.7%)	2.6
20:1 (5%)	1.7

## **SAW MASTER™**

### **Synthetic Sawing Fluid**

Specially formulated flood coolant for light to moderate-duty applications on ferrous metals and alloys

**LONGER BLADE LIFE. FASTER CUTTING.**

Lubricates and cools to get the most from your blade or tool

**REJECTS MOST TRAMP OILS**

Unwanted oils can be separated and removed to keep the fluid performing longer

**EXCELLENT SUMP LIFE**

Advanced anti-microbial agents control bacterial growth and prevent rancidity, which lowers fluid replacement costs

**CAN BE USED IN MOST HARD WATER APPLICATIONS**

Eliminates filtration problems and residue

**SURFACES CAN BE WELDED AND PAINTED OVER**

**LOW TO NON-FOAMING**



PROD NO	CONTAINER SIZE (LITER)	CONTAINERS PER CASE
1988854	5 liter	case of 2
1988855	25 liter	—
1988856	200 liter drum	—

*Not recommended for use as a spray lubricant. Mix this product with water as recommended*

RATIO	REFRACTOMETER
5:1 (20%)	6.4
10:1 (10%)	3.2
15:1 (6.7%)	2.4
20:1 (5%)	1.6