

Metal Drilling

Jobber Length Drill Bits

General Purpose HSS Fractional 3/8" Reduced Shank Jobber Length Drill Bits with 118° Point (Series 738/718)



71832

- Standard general purpose bit with 3/8" reduced shank

Applications:

Automotive, maintenance and repair, stationary drill press

Sets:

Metal Index: 60147, 60148

Size	Decimal Equiv.	Flute Length	Overall Length	Carded Item #	Bulk Item #
25/64"	.3906	3-3/4"	5-1/8"	73825	71825
13/32"	.4063	3-7/8"	5-1/4"	73826	71826
27/64"	.4219	3-15/16"	5-3/8"	73827	71827
7/16"	.4375	4-1/16"	5-1/2"	73828	71828
29/64"	.4531	4-3/16"	5-5/8"	73829	71829
15/32"	.4688	4-5/16"	5-3/4"	73830	71830
31/64"	.4844	4-3/8"	5-7/8"	73831	71831
1/2"	.5000	4-1/2"	6"	73832ZR	71832

General Purpose HSS Letter Size Straight Shank Jobber Length Drill Bits (Series 401)



40101ZR

- 135° split-point tip starts drilling immediately and eliminates "walking."
- Engineered with premium high speed steel in bright finish.
- Ideal for use when large, precisely-sized holes are required. Drills exact-sized hole for tapping applications.
- Straight shank

Applications:

Automotive, maintenance and repair, portable drills, stationary drill press

Size	Decimal Equiv.	Flute Length	Overall Length	Carded Item #	Bulk Item #
Letter A	0.2340	2-5/8"	3-7/8"	—	40101ZR
Letter B	0.2380	2-3/4"	4"	—	40102
Letter C	0.2420	2-3/4"	4"	—	40103ZR
Letter D	0.2460	2-3/4"	4"	—	40104ZR
Letter E	0.2500	2-3/4"	4"	—	40105
Letter F	0.2570	2-7/8"	4-1/8"	—	40106
Letter G	0.2610	2-7/8"	4-1/8"	—	40107
Letter H	0.2660	2-7/8"	4-1/8"	—	40108ZR
Letter I	0.2720	2-7/8"	4-1/8"	—	40109ZR
Letter J	0.2770	2-7/8"	4-1/8"	—	40110ZR
Letter K	0.2810	2-15/16"	4-1/4"	—	40111ZR
Letter L	0.2900	2-15/16"	4-1/4"	—	40112
Letter M	0.2950	3-1/16"	4-3/8"	—	40113
Letter N	0.3020	3-1/16"	4-3/8"	—	40114
Letter O	0.3160	3-3/16"	4-1/2"	—	40115
Letter P	0.3230	3-5/16"	4-5/8"	—	40116
Letter Q	0.3320	3-7/16"	4-3/4"	—	40117
Letter R	0.3390	3-7/16"	4-3/4"	—	40118
Letter S	0.3480	3-1/2"	4-7/8"	—	40119ZR
Letter T	0.3580	3-1/2"	4-7/8"	—	40120
Letter U	0.3680	3-5/8"	5"	—	40121
Letter V	0.3770	3-5/8"	5"	—	40122
Letter W	0.3860	3-3/4"	5-1/8"	—	40123
Letter X	0.3970	3-3/4"	5-1/8"	—	40124
Letter Y	0.4040	3-7/8"	5-1/4"	—	40125
Letter Z	0.4130	3-7/8"	5-1/4"	—	40126