

### Door Lock Installation Kits



3111002 (3111002C\*)

- Self-centering jig fits all common door widths
- Adjustable for both 2-3/8" and 2-3/4" backsets
- Complete installation in 3 easy steps

### Jig Saw Blades



3071412



3072410D

- Wood cutting: precision-ground teeth for fast smooth cutting in hard and soft wood, plastics, laminate particle board and plywood
- Metal cutting: fully hardened teeth for cutting ferrous and non-ferrous metals, aluminum and sheet steel

LINEAR EDGE

### Portable Band Saw Blades



3074000P3

- Shatter resistant, bi-metal construction for extended life
- 8% Cobalt content for added durability
- Electron beam weld construction provides flexibility

Door Width	Backset	Door Type	Hole Saw Type	U.S. Item #	Canadian Item #
1-1/4" or 1-3/4"	2-3/8" or 2-3/4"	Wood	Carbon Steel	3111001	3111001C
1-1/4" or 1-3/4"	2-3/8" or 2-3/4"	Wood or Metal	Bi-Metal	3111002	3111002C

Blade Length	TPI	Blade Material	Tooth Design	Carded Item # (2-pk)
<b>U-Shank</b>				
3"	—	5/32 Carbide Grit	—	3071300
3-1/4"	10	Bi-Metal	Milled	3071314
3-1/4"	20	Bi-Metal	Milled	3071320
3-1/4"	36	Bi-Metal	Milled	3071336
4"	6	Carbon	Fleam Ground	3071406
4"	10	Carbon	Milled	3071410
4"	10	Carbon	Fleam Ground	3071412
4"	10	Carbon	Fleam Ground	3071410D
6-Piece Assorted	Includes: (1) 3071320, (1) 3071314, (1) 3071406, (1) 3071412, (2) 3071410,			3071001
<b>T-Shank</b>				
3"	—	5/32 Carbide Grit	—	3072300
3"	10	Bi-Metal	Milled	3072314
3"	20	Bi-Metal	Milled	3072320
3"	36	Bi-Metal	Milled	3072336
4"	6	Carbon	Fleam Ground	3072406
4"	10	Carbon	Milled	3072410
4"	10	Carbon	Fleam Ground	3072412
4"	10	Carbon	Fleam Ground	3072410D
6-Piece Assorted	Includes: (1) 3072320, (1) 3072314, (1) 3072406, (1) 3072412, (2) 3072410,			3072001

Blade Length	TPI	Height	Blade Thickness	Item # (3-pk)	Bulk # (25-pk)
44-7/8"	10/14	1/2"	.020"	3074000P3	3074000P25
44-7/8"	14	1/2"	.020"	3074001P3	3074001P25
44-7/8"	18	1/2"	.020"	3074002P3	3074002P25
44-7/8"	24	1/2"	.020"	3074003P3	3074003P25
44-7/8"	14/18	1/2"	.020"	3074004P3	3074004P25

### Portable Band Saw Matrix

Blade Length	TPI	Recommended Thickness
44-7/8"	14	1/4" to 1/2"
44-7/8"	18	1/8" to 1/4"
44-7/8"	24	3/32" to 1/8"
44-7/8"	14/18	1/8" to 1/2"